

SATAjet® 1500 B SoLV



German Engineering

Spray Guns | Cup Systems | Breathing Protection | Air Filtration | Accessories



For more options in the
application of solvent materials

SATAjet 1500 B SoLV – The solvent solution


SATA extends an invitation to technicians using solvent paint products who would like to take advantage of SATA's quality and reliability at an affordable price. For those who have or have not used SATA spray guns before, step-up and give the SATAjet 1500 B SoLV a try.

The SATAjet 1500 B SoLV provides fine finishes with cost saving transfer efficiency, keeps the required wetting using today's **Low VOC exempt solvent basecoat** or the more traditional **National Rule solvent basecoats**. The SATAjet 1500 B SoLV is also a good choice for **clearcoat** appearance, while meeting transfer efficiency and profitability expectations.

The nozzle system of the SATAjet 1500 B SoLV meets the demands for topcoat applications and delivers even material distribution throughout the entire pattern. It offers to solvent and **Low VOC application** the flexibility painters expect from a SATA gun. The balanced design provides comfort and ergonomics, and the easy-to clean durable surface of the spray gun will work with any solvent-based material.

The SATAjet 1500 B SoLV offers the performance required to achieve quality finishes.

SATAjet® 1500B SoLV Maintenance Set #1047150



Art. No.	Description
172429	Sealing ring for air cap ring
140582	Sealing element for fluid tip
143230	Air distribution ring Extraction tool
91959	Air piston rod
133942	Seal retainer
133934	Spindle seal
133991	Air piston head
15438	Paint needle packing Seal Pressure spring for needle seal Compression screw

Nozzle size	HVLP	1.3	1.4
	RP	1.3	1.4
Standard with RPS cups 0.3 l, 0.6 l, 0.9 l, 1 ea.		1010925	1010933
		1010892	1010917
Nozzle Set		1010967	1010975
		1010941	1010959



PRODUCT BENEFITS

- Designed for Full System Application: solvent-based basecoats, either **Low VOC** or **National Rule** as well as sealer and **clearcoat**.
- Nice-sized, even spray pattern
- Wide air pressure range from 7 – 29 psi.
HVLP compliant 26 psi, RP compliant 29 psi
- Air consumption at 26 psi inlet HVLP: 12.4 cfm RP: 10.2 cfm
- Fast working speed
- Smooth anodized spray gun body
- Excellent value spray gun



Your SATA dealer



DanAm®

The exclusive independent distributor of SATA product in the US and Puerto Rico

One SATA Drive
Spring Valley, MN 55975
Phone: 800-533-8016
Fax: 800-633-7282
E-Mail: satajet@satausa.com
www.satausa.com

Errors and technical alterations reserved - SATA, SATAjet and/or other SATA products referenced herein are either registered trademarks or trademarks of SATA GmbH & Co. KG in the U.S. and/or other countries.

16 SATAjet 1500 SoLV
Printed in U.S.A.
200604