

# FEM-03

## Industrial Enclosure Options

**Pre-Wired Enclosures Make for Easy Setup & Installation.**

### Applications:

The versatile FEM-03 Flow Monitor allows you to monitor rate, totalization, limits and ratios – accurately and effectively. To complement the FEM-03, AW Gear Meters offers custom industrial enclosures that allow you to set up and operate your monitoring system more easily. Pre-wiring means you don't have to spend time soldering and looking for parts. Just plug in and power up to get started.

All units are powered by 110 VAC input. See below for features on the standard enclosure model. Refer to the back for available custom options.

Note: Remote programming and monitoring is available by adding the optional RS-232 serial output connector to the FEM-03RT-E and FEM-03AX-E.



### Standard Enclosure Model:

#### FEM-03E FLOW RATE MONITOR

Base unit has one flowmeter input, on/off switch, 110 VAC input, one FEM-03 Single-Channel unit.

### Customized Enclosure Options:

- Custom enclosure sizes available
- 2nd flowmeter input
- Intrinsic barrier(s)
- FEM-03A2 (dual channel unit)
- On/off switch
- 2nd flowmeter Input
- FEM-03A2 (dual channel unit)
- Analog output connection
- Limit output connection
- Limit lights
- Silencer pushbutton
- Buzzer
- On/off switch with LED
- External reset connection
- Gun trigger input
- Customized lights (tower lights, etc)
- Customized label
- 2nd limit output connection
- Serial output connector (RS-232 communication)

